



Product Features

- Three metal handles
- Decorative trim plate
- 2C1L handles should not be used with 3-outlet diverter valves
- To complete package, you must order G-8006 Rough Valve + 2 other Rough Valves

Code compliance

- ADA

Available Finishes

- 24K Polished Gold
- 24K Brushed Gold
- Brushed Brass PVD®
- Brushed Gold PVD®
- Architectural Black™
- Brushed Nickel
- Brushed Nickel PVD®
- Brushed Onyx PVD®
- Brushed Tuscan Bronze PVD®
- Rose Gold / Brushed Copper PVD®
- Gunmetal PVD®
- Matte Black
- Olive Bronze
- Onyx PVD®
- Polished Brass PVD®
- Polished Chrome
- Polished Gold PVD®
- Polished Nickel
- Polished Nickel PVD®
- Polished Tuscan Bronze PVD®
- Rose Gold / Polished Copper PVD®
- Satin Gold PVD®
- Steelnox® (Satin Nickel)
- Unfinished Brass
- Unfinished Brushed Brass
- Vintage Brushed Brass
- Warm Bronze PVD®
- Architectural White

* Special order finish - call for availability

Technical drawing of the G-8006 and G-8076 rough-in valves. The drawing includes top, side, and bottom views with dimensions in inches and millimeters.

Top View Dimensions:

- Overall width: 14-7/16" (366mm)
- Center-to-center spacing: 3-15/16" (100mm)
- Individual valve width: 3-1/4" (83mm)
- Overall height: 4-3/4" (120mm)
- Valve height: 2-3/8" (60mm)

Side View Dimensions:

- Overall height: 4-3/4" (120mm)
- Rough-in height: 2-3/8" (60mm)

Bottom View Dimensions:

- Overall width: 3-11/16" (89mm)
- Center-to-center spacing: 2-11/16" (68mm)

Labels:

- Rough - G-8006
- Rough - G-8076 or G-8052 or G-8053

CUTTING EDGE DESIGN