



#### Product Features

- Aerated flow rate 8 gpm @60 psi
- Handshower flow rate ?1.5 max gpm
- Deck-mounted handshower and diverter set included
- Optional in-line pressure balancing valve
- To complete package, you must order Rough Valve

#### Available Finishes

- 24K Polished Gold
- 24K Brushed Gold
- Brushed Brass PVD®
- Brushed Gold PVD®
- Architectural Black™
- Brushed Nickel
- Brushed Nickel PVD®
- Brushed Onyx PVD®
- Brushed Tuscan Bronze PVD®
- Rose Gold / Brushed Copper PVD®
- Gunmetal PVD®
- Matte Black
- Olive Bronze
- Onyx PVD®
- Polished Brass PVD®
- Polished Chrome
- Polished Gold PVD®
- Polished Nickel
- Polished Nickel PVD®
- Polished Tuscan Bronze PVD®
- Rose Gold / Polished Copper PVD®
- Satin Gold PVD®
- Steelnox® (Satin Nickel)
- Un?nished Brass
- Unfinished Brushed Brass
- Vintage Brushed Brass
- Warm Bronze PVD®
- Architectural White

\* Special order finish - call for availability

**GRAFF®**

Technical drawing of the G-1086 gas detector, showing front, side, and detail views with dimensions in inches and millimeters.

**Front View Dimensions:**

- Top width: 4-1/2" (115mm)
- Bottom width: 2-1/4" (57mm)
- Right side width: 2-1/4" (57mm)

**Side View Dimensions:**

- Top width: 3-1/2" (89mm)
- Bottom width: 2-5/8" (66mm)

**Detail View Dimensions:**

- Top width: 8-7/16" Min. (214mm)
- Bottom width: 9-1/4" Max. (236mm)
- Right side width: 2-5/16" (59mm)

**Labels:**

- G-1086
- Wall max. (89mm)
- Wall min. (66mm)
- Min. (214mm)
- Max. (236mm)