

Vintage Widespread Lavatory Faucet



- Installs on 8" centers
- Aerated flow rate ≤ 1.2 max gpm
- 1-3/16" hole cutout (x3)
- Includes push-top umbrella pop-up drain with overflow
- Optional matching decorative trap G-9973

- CALGreen

- 24K Polished Gold
- 24K Brushed Gold
- 24K Brushed Gold/Architectural Black Accents
- Architectural Black™
- Brushed Nickel
- Gunmetal PVD®
- Gunmetal Distressed
- Matte Black
- Olive Bronze
- Polished Chrome
- Polished Chrome/Architectural Black Accents
- Polished Nickel
- Polished Nickel/Architectural Black Accents
- Unfinished Brass
- Unfinished Brushed Brass
- Vintage Brushed Brass
- Architectural White

The technical drawings illustrate the dimensions of the Fire Protection Valve assembly:

- Main Assembly View:** Shows three valves mounted on a wall. Key dimensions include:
 - Valve height from mounting surface: $2\frac{7}{8}"$ (73mm).
 - Distance between valve centers: $3\text{'-}1/8"$ (80mm).
 - Top handle diameter: $\varnothing 1"$ (26mm).
 - Top handle width: $1\text{'-}15/16"$ (50mm).
 - Top handle thickness: $1/4"$ (6mm).
 - Mounting bracket diameter: $1\text{'-}3/16"$ (30mm).
 - Mounting bracket thickness: $1/4"$ (6mm).
- Side View:** Shows the side profile of the valve body with a total height of $5\text{'-}9/16"$ (140mm) and a top handle diameter of $\varnothing 1\text{'-}15/16"$ (50mm).
- Front View:** Shows the front view of the valve body with a top handle diameter of $\varnothing 2\text{'-}11/16"$ (68mm) and a total height of $7\text{'-}7/8"$ (200mm).