

Phase

GL7.690H-LM45E0-T

Wall-Mounted M-Series Thermostatic System - Tub Spout
and Handshower (Trim)

GRAFF[®]



Caractéristiques du produit

- Aerated flow rate ~7 gpm @45 psi
- Handshower flow rate ?1.5 max gpm
- 9-1/4" spout reach
- Includes handshower with 59" hose

Conformité aux codes

- ADA
- CALGreen

Finitions disponibles

- Or 24K
- Or brossé 24K
- Laiton brossé PVD®
- Or brossé PVD®
- Noir_Architectural Black™
- Nickel brossé
- Nickel brossé PVD®
- Onyx brossé PVD®
- Bronze toscan brossé PVD®
- Or Rose / Cuivre Brossé PVD®
- Gunmetal PVD®
- Matt noir
- Bronze olive
- Onyx PVD®
- Laiton poli PVD®
- Chrome poli
- Or poli PVD®
- Nickel poli
- Nickel poli PVD®
- Bronze toscan poli PVD®
- Or Rose / Cuivre Poli PVD®
- Or satiné PVD®
- Nickel satiné Steelnox®
- Laiton sans ?nition
- Laiton brut brossé
- Laiton brossé Vintage
- Warm Bronze PVD®
- Blanc

* Finition sur commande spéciale - appelez pour disponibilité

Phase

GL7.690H-LM45E0-T

Wall-Mounted M-Series Thermostatic System - Tub Spout
and Handshower (Trim)

