



Caratteristiche del prodotto

- Floor-mount installation
- Aerated flow rate ?1.2 max gpm
- Product sold only as a complete set - handle is required to install rough
- 9-13/16" spout reach
- 46-1/16" ~ spout height
- Drain assembly not included
- Includes G-1050 spout connection rough
- Includes deck-mounted handle
- Includes G-3715-LM31-**-T

Conformità al codice

- ADA
- CALGreen

Finiture disponibili

- Ottone spazzolato PVD®
- Oro spazzolato PVD®
- Nero_Architectural Black™
- Nickel spazzolato
- Nickel spazzolato PVD®
- Onyx spazzolato PVD®
- Bronzo toscano spazzolato PVD®
- Oro rosa / Rame spazzolato PVD®
- Gunmetal PVD®
- Nero opaco
- Bronzo Oliva
- Onyx PVD®
- Ottone lucido PVD®
- Cromo Lucido
- Oro lucido PVD®
- Nickel lucido
- Nickel lucido PVD®
- Bronzo toscano lucido PVD®
- Oro Rosa / Rame lucido PVD®
- Oro satinato PVD®
- Steelnox® Nickel Satinato
- Ottone naturale
- Ottone naturale spazzolato
- Ottone spazzolato Vintage
- Warm Bronze PVD®
- Bianco

* Finitura ordine speciale: richiedere disponibilità