



Caratteristiche del prodotto

- Single metal handle and decorative trim plate
- Use with G-8006 thermostatic rough valve

Conformità al codice

- ADA

Finiture disponibili

- Oro Lucido 24K
- Oro spazzolato 24K
- Ottone spazzolato PVD®
- Oro spazzolato PVD®
- Nero_Architectural Black™
- Nichel spazzolato
- Nickel spazzolato PVD®
- Onyx spazzolato PVD®
- Bronzo toscano spazzolato PVD®
- Oro rosa / Rame spazzolato PVD®
- Gunmetal PVD®
- Nero opaco
- Bronzo Oliva
- Onyx PVD®
- Ottone lucido PVD®
- Cromo Lucido
- Oro lucido PVD®
- Nickel lucido
- Nickel lucido PVD®
- Bronzo toscano lucido PVD®
- Oro Rosa / Rame lucido PVD®
- Oro satinato PVD®
- Steelnox® Nickel Satinato
- Ottone naturale
- Ottone naturale spazzolato
- Ottone spazzolato Vintage
- Warm Bronze PVD®
- Bianco

* Finitura ordine speciale: richiedere disponibilità

Solar M-Series Thermostatic Valve Trim with Handle

GRAFF®

SOLAR Series

Technical drawings of the SOLAR Series light fixture, showing side, front, and rough-in views with dimensions.

Side View (Left): Shows the profile of the fixture. The mounting bracket is labeled M4.

Front View (Middle): Shows the square face of the fixture. Dimensions include:

- Overall width: 3-15/16" (100mm)
- Overall height: 4-5/16" (110mm)
- Bottom mounting hole spacing: 1-9/16" (39mm)
- Brand name: GRAFF

Rough-In View (Right): Shows the internal wiring and mounting details. Dimensions include:

- Top mounting hole spacing: 4-5/16" (110mm) wall max. (110mm), 3-3/8" wall min. (85mm)
- Bottom mounting hole spacing: 5/16" (7.5mm)
- Side mounting hole spacing: 2" (50mm)
- Bottom mounting hole spacing: 2-9/16" (66mm)
- Label: Rough - G-5006

CUTTING EDGE DESIGN